

Mounting Brack-Its



Mounting Hardware

Used to mount traffic signs, security devices and enclosures.

- 201 grade stainless steel for superior strength
- Withstands stress and wind vibration with specially designed reinforcement ribs
- Convenient attachment methods
- Hex head bolts with metal & fibre washer, no nuts required
- Applied with BAND-IT® banding products or Ultra-Lok™ free end clamps



C001 / C003 / C075 / C400 / UL4000

See pages 23-25 for full details on TOOLS and their specifications.

Y Brack-Its Bracket width 1.5" (38mm) • Pack Qty – 50

PART NUMBER	LENGTH		HOLE DIA.		HOLE CENTRES		BAND WIDTH	
	IN	MM	IN	MM	IN	MM	IN	MM
DE096	2	51	0.311	7.9	0.75	19	0.75	19.05
DE097	4	102	0.311	7.9	1.48	37.5	0.75	19.05



DE096 / DE097

Valmount Brack-Its Pack Qty – 50

PART NUMBER	LENGTH		HOLE DIA.		HOLE CENTRES		BAND WIDTH	
	IN	MM	IN	MM	IN	MM	IN	MM
D025	5.6	142	0.375	9	1.5	38	0.75	19.05
D026	3.6	91	0.375	9	1.5	38	0.75	19.05



D025 / D026

Super Valmount Brack-Its Pack Qty – 50

PART NUMBER	LENGTH		HOLE DIA.		HOLE CENTRES		BAND WIDTH	
	IN	MM	IN	MM	IN	MM	IN	MM
MR190	7.9	200	0.375	9	1.5	38	0.75	19.05



MR190

Nameplate Brack-Its Pack Qty – 50

PART NUMBER	LENGTH		HOLE DIA.		HOLE CENTRES		BAND WIDTH	
	IN	MM	IN	MM	IN	MM	IN	MM
DE0209	1.6	42	0.2	5	1.5	38	0.5	12.7



DE0209



Mounting Brack-Its



D310 Flared Leg Mini-Brack-It

D315 Straight Leg Mini-Brack-It

D021 Single Bolt Flared leg

D001 Single Bolt Straight Leg

D008 2 Bolt Straight Leg

D007 L-Mount Right Angle Brack-It



Mini Brack-Its Stainless Steel Pack Qty – 50

PART NUMBER	DESCRIPTION	WEIGHT	
		LBS	KGS
D310	Flared Leg with SS Bolt, Fibre Washer, 1/2" (12.7mm) Slot	3.2	1.5
D315	Straight Leg with SS Bolt, Fibre Washer, 1/2" (12.7mm) Slot	3.3	1.5
D302	Replacement Bolts - SS Bolt M8 x 12 Hex head	0.75	0.34

For band widths up to 1/2" (12.7mm)

1 Bolt Flared Leg Brack-It

Thickness 0.070" (1.8mm) • Pack Qty – 50

PART NUMBER	DESCRIPTION	WEIGHT	
		LBS	KGS
D021	Stainless Steel with S.S. Bolt, and Washer	7.6	3.5
D022	Stainless Steel, no bolt or washer	6.0	2.7

For band widths up to 3/4" (19.05mm)

1 Bolt Straight Leg Brack-It

Thickness 0.070" (1.8mm) • Pack Qty – 50

PART NUMBER	DESCRIPTION	WEIGHT	
		LBS	KGS
D001	Stainless Steel with S.S. Bolt, Washer and Fibre washer	7.3	3.3
D004	Stainless Steel, no bolt or washer	5.9	2.7

For band widths up to 3/4" (19.05mm)

2 Bolt Brack-It Thickness 0.070" (1.8mm) • Pack Qty – 50

PART NUMBER	DESCRIPTION	WEIGHT	
		LBS	KGS
D008	Stainless Steel with S.S. Bolt, Washer and Fibre washer	9.6	4.4
D009	Stainless Steel, no bolt or washer	7.1	3.2

For band widths up to 3/4" (19.05mm)

L-Mount Right Angle Brack-It 0.070" (1.8mm) • Pack Qty – 50

PART NUMBER	DESCRIPTION	WEIGHT	
		LBS	KGS
D007	Solid anchor for right angle mounted signs. Bolts not inc.	4.4	2.0

Bolts and Washers for Brack-It Pack Qty – 50

PART NUMBER	DESCRIPTION	WEIGHT	
		LBS	KGS
D002	S.S. Bolts for Stainless Brack-its M8 x 20 Long Hex Head	1.25	0.57
D003	Fibre washers	0.06	0.03